

**(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)**

**(19) World Intellectual Property Organization  
International Bureau**



**(43) International Publication Date**  
**13 November 2003 (13.11.2003)**


**(10) International Publication Number**  
**WO 03/093079 A1**

**PCT**

- |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <p>(51) <b>International Patent Classification</b><sup>7</sup>: <b>B60S 1/38</b></p> <p>(21) <b>International Application Number</b>: PCT/EP03/04702</p> <p>(22) <b>International Filing Date</b>: 29 April 2003 (29.04.2003)</p> <p>(25) <b>Filing Language</b>: English</p> <p>(26) <b>Publication Language</b>: English</p> <p>(30) <b>Priority Data</b>:<br/>02076754.7                      3 May 2002 (03.05.2002)    EP</p> <p>(71) <b>Applicant</b> (<i>for all designated States except US</i>): <b>FEDERAL-MOGUL S.A.</b> [BE/BE]; Avenue Champion, B-6790 AUBANGE (BE).</p> <p>(72) <b>Inventors</b>; and</p> <p>(75) <b>Inventors/Applicants</b> (<i>for US only</i>): <b>MARMOY, Didier</b> [BE/BE]; Voie de Villers, B-08370 MARGNY (BE).</p> | <p><b>HENIN, Pierre</b> [BE/BE]; Rue de Villemont, 339, B-6730 BELLEFONTAINE (BE). <b>BOLAND, Xavier</b> [BE/BE]; Route de Luxembourg, 304, B-6700 ARLON (BE).</p> <p>(74) <b>Agent</b>: <b>HOOIVELD, Arjen, Jan, Winfried</b>; Arnold &amp; Siedsma, Sweelinckplein 1, NL-2517 GK The Hague (NL).</p> <p>(81) <b>Designated States</b> (<i>national</i>): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.</p> <p>(84) <b>Designated States</b> (<i>regional</i>): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,</p> |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

*[Continued on next page]*

**(54) Title:** WINDSCREEN WIPER DEVICE



**(57) Abstract:** A windscreen wiper device (1) comprising an elastic, elongated carrier element, as well as an elongated wiper blade (2) of a flexible material, which can be placed in abutment with a windscreen to be wiped, which wiper blade (2) includes opposing longitudinal grooves (3) on its longitudinal sides, in which grooves (3) spaced-apart longitudinal strips (4) of the carrier element are disposed, wherein neighbouring ends of said longitudinal strips (4) are interconnected by a respective connecting piece (6), which windscreen wiper device (1) comprises a connecting device (7) for an oscillating wiper arm (8), wherein said oscillating arm (8) is pivotally connected to said connecting device (7) about a pivot axis near one end, a special feature of which is that said connecting device (7) comprises engaging members (9) being welded to longitudinal sides (10) of said longitudinal strips (4) that face away from each other in such a manner as to withstand shearing forces in a direction along said longitudinal strips (4).

**WO 03/093079 A1**

**BEST AVAILABLE COPY**

WO 03/093079 A1



SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*

**Published:**

— *with international search report*

## WINDSCREEN WIPER DEVICE

5

The invention relates to a windscreen wiper device comprising an elastic, elongated carrier element, as well as an elongated wiper blade of a flexible material, which can be placed in abutment with a windscreen to be wiped, which wiper blade includes opposing longitudinal grooves on its longitudinal sides, in which grooves spaced-apart longitudinal strips of the carrier element are disposed, wherein neighbouring ends of said longitudinal strips are interconnected by a respective connecting piece, which windscreen wiper device comprises a connecting device for an oscillating wiper arm, wherein said oscillating arm is pivotally connected to said connecting device about a pivot axis near one end.

Such a windscreen wiper device is generally known. The prior art windscreen wiper device is in particular designed as a "yokeless" wiper device, wherein use is no longer made of several yokes pivotally connected to each other, but wherein the wiper blade is biased by the carrier element, as a result of which it exhibits a specific curvature. The oscillating arm of the prior art windscreen wiper device comprises a projecting pin on one side thereof, which is inserted sideways into a through hole of the connecting device.

The connecting device is attached to the unit consisting of the elongate wiper blade and the longitudinal strips through a clamping operation, wherein clamping parts of said connecting device are

CONFIRMATION COPY

clamped round longitudinal sides of the strips. In order to lock said connecting device in a direction along the longitudinal strips, said strips are each provided with a recess at their exterior longitudinal side so that the clamping parts of the connecting device rest in said recess. Obviously, cutting such a precisely shaped recess in each longitudinal strip needs additional tools and an extra step in manufacturing said windshield wiper device.

10 The object of the invention is to overcome the drawbacks of the prior art as indicated above, in particular to provide a windscreen wiper device wherein the connecting device and the unit consisting of the wiper blade and the strips are interconnected in a durable, solid manner, without the need of additional tools and an extra cutting step in the manufacturing process of the windshield wiper device.

20 In order to accomplish that objective, a windscreen wiper device of the kind referred to in the introduction is characterized in that said connecting device comprises engaging members being welded to longitudinal sides of said longitudinal strips that face away from each other in such a manner as to withstand shearing forces in a direction along said longitudinal strips. Said engaging members are welded along their entire length to the longitudinal strips or at several points along their length.

In a preferred embodiment of a windscreen wiper device according to the invention the engaging members are welded to said longitudinal sides through an ultrasonic welding operation. To this end, the connecting device and the engaging members are

preferably made in one piece of thermoplastic material (whether or not enforced by glass fibers), wherein said longitudinal strips are either entirely made of thermoplastic material as well or provided  
5 with a thermoplastic skin. In the latter case the longitudinal strips can be made by co-extrusion of a thermoplastic around a steel wire.

In another preferred embodiment of a windscreen wiper  
10 device according to the invention the end of the oscillating wiper arm includes two at least substantially cylindrical protrusions, which form bearing surfaces, at the location of the pivot axis, which protrusions extend in lateral direction with  
15 respect to the oscillating wiper arm. In another preferred embodiment the end of the oscillating wiper arm has an at least substantially U-shaped cross-section, said connecting device being partially positioned within said end of the oscillating arm,  
20 wherein the end of the oscillating arm is provided, at the location of the pivot axis, with a shaft extending between the legs of the U-shaped cross-section, said shaft pivotally engaging in said connecting device. As a result, the two  
25 protrusions/shaft that function(s) as bearing surface(s) is/are spaced far apart, so that the forces that are exerted on said bearing surface(s) will be relatively low. In particular, the protrusions/shaft can be pivotally fitted in  
30 correspondingly shaped recess(es) in the connecting device.

In another preferred embodiment of a windscreen wiper device according to the invention, the  
35 protrusions/shaft can be snapped into said recess(es).

In another preferred embodiment of a windscreen wiper device according to the invention, the protrusions/shaft are/is dimensioned such that they/it can be passed through (an) insertion opening(s) of the recess(es) from an at least substantially perpendicular position of the oscillating arm with respect to the wiper blade, and be locked in position in said recess(es) from an at least substantially parallel position of the oscillating wiper arm with respect to the wiper blade. This makes it possible to move, in particular pivot, the oscillating wiper arm from a mounting position (that is, a (vertical) position perpendicularly to the wiper blade or the plane of a windscreen to be wiped) to an operative position (that is, a (horizontal) position parallel to the wiper blade or the plane of a windscreen to be wiped). In the mounting position, the protrusions/shaft can be freely inserted into the insertion opening(s) of the recess(es) and subsequently be mounted in said recess(es), whilst in the operative position the protrusions/shaft are/is locked in position in said recess(es), so that they/it cannot move out of said recess(es) via the insertion opening(s).

In another preferred embodiment of a windscreen wiper device according to the invention, the connecting device includes a guide groove for the oscillating wiper arm. Since the oscillating wiper arm is at least partially disposed in said guide groove in the aforesaid operative position, the oscillating wiper arm comprises additional capability of withstanding relatively high torques in that position.

In another preferred embodiment of a windscreen wiper

device according to the invention, said connecting pieces are clamping members, which form separate constructional elements. In particular, said connecting pieces are form-locked ("positive locking" or "having positive fit") or force-locked to the adjacent ends of the longitudinal strips.

In another preferred embodiment of a windscreen wiper device according to the invention, said connecting pieces are in one piece with said longitudinal strips.

In another preferred embodiment of a windscreen wiper device according to the invention, at least said longitudinal strips are made of spring band material, preferably steel, coated with a thermoplastic material.

The invention furthermore relates to a method for manufacturing a windscreen wiper device according to the invention, wherein opposing longitudinal grooves are formed in the longitudinal sides of an elongated wiper blade of a flexible material, which can be placed in abutment with a windscreen to be wiped, in which grooves longitudinal strips of a carrier element are subsequently fitted in spaced-apart relationship, wherein neighbouring ends of said longitudinal strips are interconnected by a respective connecting piece, wherein an oscillating arm is pivotally connected to a connecting device of the windscreen wiper device about a pivot axis near one end thereof, characterized in that said connecting device is fitted with engaging members, which are welded to longitudinal sides of said longitudinal strips that face away from each other in such a manner as to withstand shearing forces in a

direction along said longitudinal strips.

The invention will now be explained in more detail  
with reference to figures illustrated in a drawing,  
5 wherein:

- Figure 1 is a perspective, schematic view of a preferred embodiment of a windscreen wiper device according to the invention;
- 10 - Figures 2 and 3 show details of the windscreen wiper device of Figure 1, wherein various successive steps for fitting an oscillating wiper arm to a connecting device of the windscreen wiper device of Figure 1;
- 15 - Figures 4, 5 and 6 correspond to figures 1, 2 and 3, respectively, but relating to another preferred embodiment;
- Figure 7 corresponds to figure 5, but relating to a further preferred embodiment; and
- 20 - Figures 8 and 9 refer to a cross-sectional view of the connecting device of the windscreen wiper device of Figure 1, before and after a preferred additional retention operation to hold said connection device into position, respectively.

25

Figures 1, 2 and 3 show a preferred variant of a windscreen wiper device 1 according to the invention. Said windscreen wiper device is built up of an elastomeric wiper blade 2, in the longitudinal sides  
30 of which opposing longitudinal grooves 3 are formed, and of longitudinal strips 4 made of spring band steel, which are fitted in said longitudinal grooves 3. Said strips 4 form a flexible carrier element for the rubber wiper blade 2, as it were, which is thus  
35 biased in a curved position (the curvature in operative position being that of a windscreen to be



wiped). Neighbouring ends 5 of strips 4 are interconnected on either side of the windscreen wiper device 1 by means of connecting pieces 6 functioning as clamping members. In this embodiment, the

5 connecting pieces 6 are separate constructional elements, which may be form-locked ("positive locking" or "having positive fit") as well as force-locked to the ends 5 of strips 4. In another

10 one piece with the strips 4 made of spring band steel. In the latter case said connecting pieces form transverse bridges for the strips 4, as it were.

The windscreen wiper device 1 is furthermore built up

15 of a connecting device 7 of plastic material for an oscillating wiper arm 8. Connecting device 7 comprises engaging members 9 that are integral therewith, which are welded to longitudinal sides 10 of the strips 4 that face away from each other, as a

20 result of which the connecting device 7 is firmly attached to the unit consisting of wiper blade 2 and strips 4. In this respect it is noted that the connecting device 7 is made of a thermoplastic material and the strips 4 are made of steel with a

25 thermoplastic skin (coating). The engaging members 9 engage around said strips 4 or -in other words- said strips 4 are mounted in grooves formed by the engaging members 9. The oscillating wiper arm 8 is pivotally connected to the connecting device 7 about

30 a pivot axis near one end, and that in the following manner. The end of oscillating wiper arm 8 includes two at least substantially cylindrical protrusions 11, which form bearing surfaces, at the location of the pivot axis. Said protrusions 11 can be readily

35 inserted into correspondingly shaped recesses 12 in the connecting device 7 from a vertical position of

the oscillating wiper arm 8. This can take place freely from said vertical position, because the width of said protrusions 11 is smaller than that of the insertion openings 13 of the recesses 12 in that position: it so happens that both protrusions 11 have a flat guide surface 14 (Figure 2). Then the oscillating wiper arm 8 is pivoted through 90 degrees about the pivot axis, from its vertical position to a horizontal position (Figure 3). In the horizontal position of the oscillating wiper arm 8, the width of said protrusions 11 is smaller than the width of the insertion openings 13 of recesses 12, so that the oscillating wiper arm 8 is locked with respect to the connecting device 7 in that position (Figure 3). Figures 2 and 3 clearly show that the connecting device 7 includes a longitudinal guide groove or guide slot 15, in which the end of the oscillating wiper arm 8 rests in its horizontal position. In another preferred variant, the protrusions 11 can be snapped, that is, clipped into said recesses. Possibly, a spoiler 16 is furthermore provided.

As already mentioned above, figures 4, 5 and 6 correspond to figures 1, 2 and 3, respectively, but relating to another preferred embodiment, wherein corresponding parts are designated with the same reference numerals.

The end of oscillating wiper arm 8 has an at least substantially U-shaped cross-section at the location of its connection to the connecting device 7. On both sides of the legs of the U-shaped cross-section the end of oscillating wiper arm 8 includes two at least substantially cylindrical, inwardly extending protrusions 11, which form cylindrical bearing surfaces, at the location of the pivot axis. Said

protrusions 11 can also be readily inserted into a correspondingly shaped recess 12 in the connecting device 7 from a vertical position of the oscillating wiper arm 8. This again can take place freely from  
5 said vertical position, because also in this case the width of said protrusions 11 is smaller than that of the insertion opening 13 of the recess 12 in that position: both protrusions 11 have a flat guide surface 14 (Figure 5). Then the oscillating wiper arm  
10 8 is pivoted through 90 degrees about the pivot axis, from its vertical position to a horizontal position (Figure 6). In the horizontal position of the oscillating wiper arm 8, the width of said protrusions 11 is larger than the width of the  
15 insertion opening 13 of the recess 12, so that the oscillating wiper arm 8 is locked with respect to the connecting device 7 in that position (Figure 6). In another preferred variant, the protrusions 11 can be snapped, that is, clipped into said recess 12.  
20 Instead of one recess 12 as shown, also two recesses (one for each protrusion 11) may be used.

Figure 7 corresponds with figure 5, wherein parts corresponding with parts of figure 5 are designated  
25 with the same reference numerals. Instead of two protrusions 11 extending between both legs of the U-shaped cross-section 1, now use is made of a pin 17 extending from one leg to the other leg of the U-shaped cross-section. The way of connecting the  
30 oscillating arm 8 to the connecting device 7 is identical to the way described in relation to figures 5 and 6.

In order to prevent the occurrence of wear on  
35 protrusions 11 or pin 17, said protrusions or pin are preferably each fitted with a joint part or spacer of

a wear-resistant plastic material, which surrounds said protrusions or pin, so that the pivoting movement of connecting device 7 and oscillating wiper arm 8 with respect to each other takes place substantially without friction. Such a joint part is not necessarily mounted entirely around said protrusions or pin: only these parts of said protrusions or said pin that during use make mechanical contact with (parts of) the connecting device 7 are surrounded by a joint part. When using joint parts said protrusions 11 or said pin may have an entirely round form (i.e. without a guide surface), seen in cross-section. Preferably, the end of the oscillating arm 8 that rests in the guide groove 15 shown in figure 2 is also surrounded by a joint part or spacer of a wear-resistant plastic material.

In a preferred embodiment the connecting device 7 is firmly retained onto the wiper blade 2 through a retention operation comprising the following steps: a warm stamp 18 is moved downwardly, thus ensuring an (ultrasonic) deformation of the plastic material of the connecting device 7 onto the elastomeric material of the wiper blade 2. In other words, the head 19 of the elastomeric wiper blade 2 is "squeezed" between plastically deformed material of the connecting device 7. Figure 8 refers to a situation before the welding step of the warm stamp 18, whereas figure 19 relates to a situation (ultrasonically) after that welding step.

In another preferred embodiment the connecting pieces 6 designed as separate constructional elements being made of a thermoplastic material are welded to the longitudinal sides 10 of the strips 4 being made of

steel with a thermoplastic skin (coating).

The invention is not restricted to the variants as shown in the drawing, but it also extends to other embodiments that fall within the scope of the

5 appended claims.

## CLAIMS

1. A windscreen wiper device (1) comprising an  
elastic, elongated carrier element, as well as  
5 an elongated wiper blade (2) of a flexible  
material, which can be placed in abutment with a  
windscreen to be wiped, which wiper blade (2)  
includes opposing longitudinal grooves (3) on  
its longitudinal sides, in which grooves spaced-  
10 apart longitudinal strips (4) of the carrier  
element are disposed, wherein neighbouring ends  
of said longitudinal strips (4) are  
interconnected by a respective connecting piece  
(6), which windscreen wiper device (1) comprises  
15 a connecting device (7) for an oscillating wiper  
arm (8), wherein said oscillating arm is  
pivotally connected to said connecting device  
(7) about a pivot axis near one end,  
characterized in that said connecting device (7)  
20 comprises engaging members (9) being welded to  
longitudinal sides (10) of said longitudinal  
strips (4) that face away from each other in  
such a manner as to withstand shearing forces in  
a direction along said longitudinal strips (4).  
25
2. A windscreen wiper device according to claim 1,  
wherein said engaging members (9) are welded to  
said longitudinal sides (10) through an  
ultrasonic welding operation.  
30
3. A windscreen wiper device according to claim 1  
or 2, wherein said connecting device (7) and  
said engaging members (9) are made in one piece.
- 35 4. A windscreen wiper device according to claim 1,  
2 or 3, wherein the end of the oscillating wiper

arm (8) includes two at least substantially  
cylindrical  
protrusions (11), which form bearing surfaces,  
at the location of the pivot pin, which  
5 protrusions extend in lateral direction with  
respect to the oscillating wiper arm (8).

5. A windscreen wiper device according to claim 1,  
2 or 3, wherein the end of the oscillating wiper  
10 arm (8) has an at least substantially U-shaped  
cross-section, said connecting device (7) being  
partially positioned within said end of the  
oscillating arm (8), and wherein the end of the  
oscillating arm (8) is provided, at the location  
15 of the pivot axis, with a shaft extending  
between the legs of the U- shaped cross-  
section, said shaft pivotally engaging in said  
connecting device (7).

20 6. A windscreen wiper device according to claim 4  
or 5, wherein said protrusions (11)/said shaft  
can be pivotally mounted in (a) correspondingly  
shaped recess(es) (12) in the connecting device  
(7).

25 7. A windscreen wiper device according to claim 6,  
wherein said protrusions (11)/said shaft can be  
snapped into said recess(es) (12).

30 8. A windscreen wiper device according to claim 6,  
wherein said protrusions (11)/said shaft are/is  
dimensioned such that they/it can be passed  
through (an)insertion opening(s) (13) of the  
recess(es) (12) from an at least substantially  
35 perpendicular position of the oscillating arm  
(8) with respect to the wiper blade (2), and be

locked in position in said recess(es) (12) from an at least substantially parallel position of the oscillating wiper arm (8) with respect to the wiper blade (2).

5

9. A windscreen wiper device according to any one of the preceding claims 1 - 8, wherein said connecting pieces (6) are clamping members, which form separate constructional elements.

10

10. A windscreen wiper device according to claim 9, wherein said connecting pieces (6) are form-locked or force-locked to the adjacent ends of said longitudinal strips (4).

15

11. A windscreen wiper device according to any one of the preceding claims 1 - 8, wherein said connecting pieces (6) are in one piece with said longitudinal strips (4).

20

12. A windscreen wiper device according to any one of the preceding claims 1 - 11, wherein at least said longitudinal strips (4) are made of spring band material.

25

13. A method for manufacturing a windscreen wiper device according to any one of the preceding claims 1 - 9, wherein opposing longitudinal grooves (3) are formed in the longitudinal sides of an elongated wiper blade (2) of a flexible material, which can be placed in abutment with a windscreen to be wiped, in which grooves longitudinal strips (4) of a carrier element are subsequently fitted in spaced-apart relationship, wherein neighbouring ends of said longitudinal strips (4) are interconnected by a

30

35



respective connecting piece (6), wherein an  
oscillating arm (8) is pivotally connected to a  
connecting device (7) of the windscreen wiper  
device (1) about a pivot axis near one end  
5 thereof, characterized in that said connecting  
device (7) is fitted with engaging members (9),  
which are welded to longitudinal sides (10) of  
said longitudinal strips (4) that face away from  
each other in such a manner as to withstand  
10 shearing forces in a direction along said  
longitudinal strips (4).

1/6






FIG.1

2/6






FIG. 4




FIG. 5




FIG. 6




FIG. 7

BEFORE WELDING




FIG. 8

AFTER WELDING




FIG. 9

## INTERNATIONAL SEARCH REPORT

International Application No.  
PCT/EP 03/04702

A. CLASSIFICATION OF SUBJECT MATTER  
IPC 7 B60S1/38

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)  
IPC 7 B60S

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, WPI Data, PAJ

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 02 04269 A (LENZEN OLIVER ; SCHMID ECKHARDT (DE); SCHOLL WOLFGANG (DE); ERNSTME) 17 January 2002 (2002-01-17)	1,3,9-13
Y	page 11, paragraph 2 -page 16, paragraph 4; figures	2,5-8
Y	US 6 192 546 B1 (KOTLARSKI THOMAS) 27 February 2001 (2001-02-27)	2
A	column 4, line 52 -column 5, line 6; figures	1,3,12,13
Y	WO 01 30622 A (BLOCK PETER DE ; BOSCH GMBH ROBERT (DE)) 3 May 2001 (2001-05-03)	5-8
	page 5, line 15 -page 8, line 14; figures	
	--- -/--	



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

## \* Special categories of cited documents:

- \*A\* document defining the general state of the art which is not considered to be of particular relevance
- \*E\* earlier document but published on or after the international filing date
- \*L\* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- \*O\* document referring to an oral disclosure, use, exhibition or other means
- \*P\* document published prior to the international filing date but later than the priority date claimed

\*T\* later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

- \*X\* document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone
- \*Y\* document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.
- \*G\* document member of the same patent family

Date of the actual completion of the international search

18 July 2003

Date of mailing of the international search report

28/07/2003

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2  
NL - 2280 HV Rijswijk  
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,  
Fax: (+31-70) 340-3016

Authorized officer

Blandin, B



## INTERNATIONAL SEARCH REPORT

Int'l Application No  
PCT/EP 03/04702

## C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	US 3 659 309 A (BESNARD MARCEL) 2 May 1972 (1972-05-02) column 3, line 1 -column 4, line 9; figures 3,4 -----	4,6-8

## INTERNATIONAL SEARCH REPORT

 International Application No  
 PCT/EP 03/04702

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0204269	A	17-01-2002	DE 10033779 A1 WO 0204269 A1	02-05-2002 17-01-2002
US 6192546	B1	27-02-2001	DE 19718490 A1 BR 9804878 A CN 1102114 B WO 9850261 A1 DE 59806520 D1 EP 0914269 A1 JP 2000513677 T KR 2000022376 A US 2001004783 A1	05-11-1998 24-08-1999 26-02-2003 12-11-1998 16-01-2003 12-05-1999 17-10-2000 25-04-2000 28-06-2001
WO 0130622	A	03-05-2001	DE 29918961 U1 BR 0007263 A CN 1335814 T CZ 20012383 A3 WO 0130622 A1 EP 1152931 A1 JP 2003512249 T	08-03-2001 16-10-2001 13-02-2002 12-12-2001 03-05-2001 14-11-2001 02-04-2003
US 3659309	A	02-05-1972	NONE	

**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**